

Usitr BSP



Maksimaalne temperatuur (°C) 110

Minimaalne temperatuur (°C) -30

Tootekood	Suurus (tollides)	Keerme tüüp	Keere	Kaal (kg)
56010102	1/8"	G	G 1/8"	-
56010102V	1/8"	G	G 1/8"	-
56010104	1/4"	G	G 1/4"	-
56010104V	1/4"	G	G 1/4"	-
56010106	3/8"	G	G 3/8"	-
56010106V	3/8"	G	G 3/8"	-
56010108	1/2"	G	G 1/2"	-
56010108V	1/2"	G	G 1/2"	-
56010110	5/8"	G	G 5/8"	-
56010112	3/4"	G	G 3/4"	0.01
56010112V	3/4"	G	G 3/4"	0.01
56010116	1"	G	G 1"	0.01
56010116V	1"	G	G 1"	0.01
56010120	1 1/4"	G	G 1 1/4"	0.01
56010120V	1 1/4"	G	G 1 1/4"	0.01
56010124	1 1/2"	G	G 1 1/2"	0.01
56010124V	1 1/2"	G	G 1 1/2"	0.01
56010132	2"	G	G 2"	0.02
56010132V	2"	G	G 2"	0.03
56010140	2 1/2"	G	G 2 1/2"	0.04
56010148	3"	G	G 3"	0.04

