

Radiator flex, corrugated cooling hose



Product group	140
Safety factor	1:3
Bundled pipes/hoses	1
Cover tube resistance	, ,
Antistatic wire	
Flat coil	
Max temperature (°C)	120
Min temperature (°C)	-40

The hose is used as a cooling hose in vehicles where there is a requirement for high flexibility. Its special corrugation allows hard bends without folding. Also used as a hot water hose in the industry.

	Bend radius (mm)	Working pressure (MPa)	Vacuum pr. Max%	ID (mm)	Length meter per coil	OD (mm)	Weight (kg)
14095008	50	0.5	80	13	40	22	0.35
14095010	60	0.5	80	16	40	25	0.39
14095012	70	0.5	80	20	40	29	0.46
14095014	75	0.5	80	22	40	31	0.52
14095016	85	0.5	80	25	40	34	0.57
14095020	105	0.5	80	32	40	41	0.75
14095022	115	0.5	80	35	40	44	0.81
14095024	130	0.5	80	38	40	47	0.87
14095026	140	0.5	80	42	40	51	0.95
14095030	150	0.5	80	45	40	54	1
14095032	165	0.5	80	51	40	60	1.12
14095039	200	0.5	80	60	40	70	1.7
14095040	210	0.5	80	63	40	73.5	1.8
14095044	220	0.5	80	70	40	80	1.87
14095048	250	0.5	80	76	40	86	2
14095051	270	0.5	80	80	40	90	2.15
14095064	340	0.5	80	102	40	113	2.7

