

Blue silicon hose



Product group	140
Safety factor	1:3
Bundled pipes/hoses	1
Flat coil	
Antistatic wire	
Max temperature (°C)	180
Min temperature (°C)	-50

Excellent hose for cool and heat systems in buses and trucks. The silicon may come into contact with oil, but should NOT be used as a transporter hose for petroleum products, nor in oil baths.

	Working pressure (MPa)	ID (mm)	Length meter per coil	OD (mm)	Reinforcement layers	Weight (kg)
15091004	0.88	6	1	15	-	0.31
15091006	0.83	10	1	19	-	0.34
15091008	0.79	13	1	21	-	0.36
15091010	0.75	16	1	25	-	0.43
15091011	0.67	18	1	27	-	0.46
15091012	0.66	19	1	28	-	0.48
15091014	0.61	22	1	31	-	0.54
15091016	0.58	25	1	34	-	0.59
15091018	0.57	28	1	37	-	0.63
15091019	0.55	30	1	39	-	0.68
15091020	0.53	32	1	41	-	0.72
15091022	0.51	35	1	44	-	0.76
15091024	0.49	38	1	47	-	0.79
15091025	0.48	40	1	50	-	0.81
15091026	0.4	41	1	49.4	-	0.83
15091030	0.47	45	1	54	-	0.87
15091031	0.33	48	1	57	-	0.95
15091032	0.37	51	1	60	-	1.05
1509103240	0.23	51	1	60	4	1.29



	Working pressure (MPa)	ID (mm)	Length meter per coil	OD (mm)	Reinforcement layers	Weight (kg)
15091038	0.31	55	1	65	-	1.21
15091039	0.27	60	1	70	-	1.29
15091040	0.23	64	1	73	-	1.35
15091044	0.22	70	1	80	-	1.49
15091048	0.21	76	1	86	-	1.58
15091051	0.18	80	1	90	-	1.66
15091053	0.17	83	1	93	-	1.72
15091056	0.15	89	1	100	-	1.85
15091064	0.13	102	1	113	-	2.32
15091072	0.2	114	1	122.4	-	0.1
15091080	0.11	127	1	138	-	2.86
15091096	0.09	152	1	163	-	3.42