

Low-weight spiral suction hose



Product group	140
Safety factor	1:3
Bundled pipes/hoses	1
Antistatic wire	
Flat coil	
Max temperature (°C)	60
Reinforcement layers	1
Min temperature (°C)	-5

A low-weight PVC hose for suction and pressure applications. The hose is also suitable for powder transportation within agriculture, food industry and gardening. Smooth inner tube. Sustains alcohols beneath 28%. Available in antistatic version, see 1552-10.

	Bend radius (mm)	Working pressure (MPa)	Vacuum pr. Max%	ID (mm)	Length meter per coil	OD (mm)	Weight (kg)
15520012	80	0.7	70	20	50	27	0.28
15520016	100	0.7	70	25	50	31	0.35
15520019	120	0.5	70	30	50	37	0.41
15520020	128	0.5	70	32	50	39	0.46
15520024	152	0.5	70	38	50	45	0.57
15520025	160	0.5	70	40	50	47	0.59
15520030	200	0.6	70	45	50	52	0.78
15520032	200	0.5	70	50	50	58	0.83
15520040	260	0.4	70	65	50	74	1
15520044	280	0.4	70	70	50	79	1.13
15520048	300	0.4	70	76	50	85	1.45
15520056	415	0.6	70	90	25	100	1.75
15520064	400	0.3	70	100	25	115	2.15
15520069	440	0.3	50	110	25	122	2.25
15520080	690	0.4	50	127	25	138	3.65
15520096	800	0.3	50	152	25	164	5.1
15520200	1,250	0.3	50	203	10	217	7.85

