

EXHAUST HOSE FOR HOT AIR, SILICONE, SINGLE COATED



Product group	140
Bundled pipes/hoses	1
Cover tube resistance	,
Antistatic wire	
Flat coil	
Max temperature (°C)	300
Reinforcement layers	1
Min temperature (°C)	-50

A hose suitable for transportation of hot steams, smoke and exhaust gases. Low-weight and extremely flexible, good in tight areas. The hose is non-inflammable and has good chemical resistance. Other dimensions are available on request.

	Bend radius (mm)	Working pressure (MPa)	ID (mm)	Vacuum pr. Max%	Length meter per coil	Weight (kg)
15620016	17	0.15	25	5	4	0.12
15620020	17	0.15	32	5	4	0.16
15620029	26	0.15	44	4	4	0.21
15620032	30	0.15	51	4	4	0.25
15620040	36	0.13	63	4	4	0.31
15620048	42	0.11	76	3	4	0.42
15620055	49	0.11	89	3	4	0.5
15620064	55	0.11	102	2	4	0.56
15620080	69	0.09	127	2	4	0.8
15620096	81	0.08	152	1	4	1.04
15620180	96	0.06	180	1	4	1.21
15620203	107	0.06	203	1	4	1.39
15620254	132	0.04	254	0.5	4	2
15620305	158	0.01	305	0.3	4	2.41

