

# Cejn series 115 nipples



|                             |                    |
|-----------------------------|--------------------|
| <b>Product info</b>         | Series 115, 80 MPa |
| <b>Product group</b>        | 531                |
| <b>Flow (l/min)</b>         | 6                  |
| <b>Locking sleeve</b>       |                    |
| <b>Security lock</b>        |                    |
| <b>Burst pressure (bar)</b> | 280                |
| <b>Bulkhead</b>             |                    |
| <b>Valve</b>                |                    |
| <b>Eliminator</b>           |                    |

CEJN Series 115 offers a Flat-Face design and a patented auto-lock function. The couplings are light in weight with an aluminum back part, making the series ideal for applications in which lightweight components are a requirement.

|                    | Hex (mm) | Thread type | Working pressure (MPa) | Thread          | Dimension (Inch) | Dimension (mm) | CEJN description | Weight (kg) |
|--------------------|----------|-------------|------------------------|-----------------|------------------|----------------|------------------|-------------|
| <b>5C101156202</b> | 22       | G           | 80                     | G 1/4" Female   | 1/4"             | 24.7           | 10 115 6202      | 0.07        |
| <b>5C101156204</b> | 24       | G           | 80                     | G 3/8" Female   | 3/8"             | 26.7           | 10 115 6204      | 0.07        |
| <b>5C101156402</b> | 22       | NPT         | 80                     | NPT 1/4" Female | 1/4"             | 25.4           | 10 115 6402      | 0.06        |
| <b>5C101156404</b> | 24       | NPT         | 80                     | NPT 3/8" Female | 3/8"             | 27.7           | 10 115 6404      | 0.07        |
| <b>5C101156454</b> | 17       | NPT         | 80                     | NPT 3/8" Male   | 3/8"             | 19.6           | 10 115 6454      | 0.59        |

