

Metal hose, parallel wrapped



Product group	140
Safety factor	1:4
Flat coil	
Antistatic wire	
Max temperature (°C)	550
Min temperature (°C)	-200

Metal hose suitable for hot oils, chemicals, gases, exhaust gases, water, steam, vacuum etc. The hose can also be used as mechanical cable protection. Inner tube: Stainless steel (1.4541 EN 10088-1) Suffix F Stainless steel (1.4404 EN 10088-1) Suffix S

	Working pressure (MPa)	ID (mm)	OD (mm)	Bend radius (mm)	Weight (kg)
14840104S	15	6.3	13.3	125	0.17
14840106S	7.5	10.6	17.5	190	0.24
14840108F	7	12.3	19.5	210	0.29
14840108S	7	12.3	19.5	210	0.3
14840110F	6.5	15.7	25.2	285	0.37
14840110S	6.5	15.7	25.2	285	0.4
14840112F	5	19.8	30.3	310	0.52
14840116F	4	25.8	36	375	0.66
14840116S	4	25.8	36	375	0.66
14840120F	3.5	33	45.7	405	1
14840124S	3	40	54	480	1.16
14840132S	2.5	51.6	67.5	550	1.56
14840140F	2	66	87.9	675	2.47
14840140S	2	66	87.9	675	2.47
14840148F	1.8	76.6	100	750	2.89
14840164F	1.4	103	128	920	4.14
14840180F	1.25	127.5	154.5	1,160	5.83
14840180S	1.25	127.5	154.5	1,160	5.77

